Preliminary results on Quasi-geoid of Latvia using Vertical Deflection observations







Overall Information

In terms of "Development of the high accuracy gravity field model for Latvia including sea territory" project main task is to compute gravity field and precise quasi-geoid model up to 1 cm accuracy using all available data.

In the year of 2016 quasi-geoid model for Eastern part of Latvia has been computed using DFHRS (Digital Finite-element Height Reference Surface) software v.4.2., which allowed the combination of GNSS/levelling data together with global geopotential models.



The research is funded by ERDF Project: 1.1.1.1/16/A/160



Overall Information

At the moment Institute of Geodesy and Geoinformatics (GGI) is dealing with new kind of measurements – vertical deflection (VD) observations – which are possible to use in DFHRS v.4.3.

DFHRS v.4.3. allows to use GNSS/levelling data together with geopotential models and field vertical deflections measurements and/or vertical deflections derivatives from geopotential models.

Vertical deflection measurements allow to check independently the places that have inconsistencies and improve quasi-geoid model.





Digital Zenith Camera

Zenith camera consists of a rotating platform, on which is mounted a small telescope, equipped with imaging device, tiltmeter, leveling mechanism, rotation gear and control equipment.

Similar platform bellow is used as base of levelling and rotation, it is mounted on field tripod.

The CCD camera is attached in direct focus, below the telescope.

A 203 mm catadioptric telescope equipped with CCD camera is used for image acquisition.

The camera has 8 Mpix sensor with 4.5 μ m pixels; at 2 m focus distance resulting field of view is 0.5x0.39 deg with resolution close to 0.5 "/pix





The research is funded by ERDF Project: 1.1.1.1/16/A/160



European Regional Development Fund

Digital Zenith Camera

Digital-Zenith camera and processing software was developed by GGI and these observations are actively done in Latvia now. The current amount of VD observations is more than 115 and precision of these measurements are evaluated as 0.10 arcsec mostly for all observations.

In terms of a project, 230 GNSS/levelling points were observed by GGI. 1st and 2nd order levelling data and 147 GNSS/levelling points were provided by LGIA.



The research is funded by ERDF Project: 1.1.1.1/16/A/160



The scheme of GNSS/levelling and VD observations



The research is funded by ERDF Project: 1.1.1.1/16/A/160

Gravity measurements with CG-6





The research is funded by ERDF Project: 1.1.1.1/16/A/160





Gravity measurements

The research is funded by ERDF Project: 1.1.1.1/16/A/160

5th EUPOS® Council and Technical Meeting, Tallinn, Estonia, 14-15 November 2018

All data



GNSS reference data improvement



	Tracked		Constellation	
	#	Satellites	#	Satellites
GPS	11	1, 3, 11, 14, 17, 18, 19, 22, 23, 31, 32	32	1, 2, 3, 532 Unhealthy: 4
GLONASS	8	1, 2, 3, 10, 11, 17, 18, 24	24	124
Galileo	6	2, 7, 12, 19, 20, 26	22	15, 7, 8, 9, 12, 14, 19, 24, 25, 26, 30, 31 Unhealthy: 11, 18, 20, 21, 22, 27
QZSS	1	194	4	193, 194, 195, 199
BeiDou	3	5, 9, 16	26	114, 16, 19 Unhealthy: 17, 2024, 2730
IRNSS	1	6	7	6 Unhealthy: 15, 7
SBAS	3	128:GAGAN - GSAT 10 127:GAGAN - GSAT 8 136:EGNOS - SES-5		
MSS	1	ESAT_		

2018-11-08T10:46:36Z (UTC)



The research is funded by ERDF Project: 1.1.1.1/16/A/160



Thank You





